

SCHULTE BUILDING SYSTEMS

PBU PANEL

SECTION PROPERTIES									
PANEL	Fy (KSI)	WEIGHT (PSF)	POSITIVE BENDING			NEGATIVE BENDING			
			lxe (IN.4/FT.)	Sxe (IN.3/FT.)	Maxo (KIP-IN.)	lxe (IN.4/FT.)	Sxe (IN.3/FT.)	Maxo (KIP-IN.)	
26	60*	0.83	0.0197	0.0363	1.3057	0.0130	0.0310	1.1147	

* Fy is 80-ksi reduced to 60-ksi in accordance with the 2007 edition of the North American Specification For Design Of Cold-Formed Steel Structural Members

NOTES:

1. All calculations for the properties of PBU panels are calculated in accordance with the 2007 edition of the North American Specification For Design Of Cold-Formed Steel Structural Members.
2. lxe is for deflection determination.
3. Sxe is for bending.
4. Maxo is allowable bending moment.
5. All values are for one foot of panel width.

**ALLOWABLE UNIFORM LOADS IN POUNDS PER SQUARE FOOT
26 Gauge PBU Panel**

SPAN TYPE	LOAD TYPE	SPAN IN FEET													
		1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5
SINGLE	NEGATIVE WIND LOAD	743.1	330.3	142.0	72.7	42.1	26.5	17.8	12.5	9.1	6.8	5.3	4.1	3.3	2.7
	POSITIVE WIND/LIVE LOAD L/180	378.2	252.1	189.1	110.0	63.7	40.1	26.9	18.9	13.8	10.3	8.0	6.3	5.0	4.1
	POSITIVE WIND/LIVE LOAD L/120	378.2	252.1	189.1	139.3	95.5	60.2	40.3	28.3	20.6	15.5	11.9	9.4	7.5	6.1
2-SPAN	NEGATIVE WIND LOAD	608.8	299.3	175.3	114.5	80.4	59.5	42.8	30.0	21.9	16.5	12.7	10.0	8.0	6.5
	POSITIVE WIND/LIVE LOAD L/180	276.8	184.5	138.4	110.7	82.6	60.7	46.4	36.7	29.7	24.6	19.2	15.1	12.1	9.8
	POSITIVE WIND/LIVE LOAD L/120	276.8	184.5	138.4	110.7	82.6	60.7	46.4	36.7	29.7	24.6	20.6	17.6	15.2	13.2
3-SPAN	NEGATIVE WIND LOAD	711.3	360.2	214.1	137.2	79.4	50.0	33.5	23.5	17.2	12.9	9.9	7.8	6.3	5.1
	POSITIVE WIND/LIVE LOAD L/180	314.5	209.7	157.3	125.8	103.2	75.7	50.7	35.6	26.0	19.5	15.0	11.8	9.5	7.7
	POSITIVE WIND/LIVE LOAD L/120	314.5	209.7	157.3	125.8	103.2	75.8	58.1	45.9	37.2	29.3	22.5	17.7	14.2	11.5
4-SPAN	NEGATIVE WIND LOAD	679.4	340.7	201.5	132.3	84.3	53.1	35.6	25.0	18.2	13.7	10.5	8.3	6.6	5.4
	POSITIVE WIND/LIVE LOAD L/180	302.7	201.8	151.3	121.1	96.4	70.8	53.8	37.8	27.6	20.7	15.9	12.5	10.0	8.2
	POSITIVE WIND/LIVE LOAD L/120	302.7	201.8	151.3	121.1	96.4	70.8	54.2	42.8	34.7	28.7	23.9	18.8	15.1	12.2

NOTES:

- 1) Section properties and allowable loads were computed in accordance with the 2007 edition of the North American Specification For Design Of Cold-Formed Steel Structural Members.
- 2) Allowable loads are based on uniform span lengths.
- 3) LIVE LOAD is limited by bending, shear, combined shear & bending and web crippling and deflection of L/180 or L/120.
- 4) NEGATIVE WIND LOAD is limited by bending, shear, combined shear and bending and deflection of L/180.
- 5) NEGATIVE WIND LOAD does not consider fastener pullout & pullover. Connection to framing must be evaluated for fastener pullout & pullover.
- 6) The weight of the panel has not been deducted from the allowable loads.

